



Facility location models for distribution system design

Andreas Klose ^{a,b,*}, Andreas Drexl ^c

^a *Universität St. Gallen, 9000 St. Gallen, Switzerland*

^b *Institut für Operations Research, Universität Zürich, 8015 Zürich, Switzerland*

^c *Christian-Albrechts-Universität zu Kiel, Olshausenstr. 40, 24118 Kiel, Germany*

Received 1 October 2001; accepted 14 October 2003

Abstract

The design of the distribution system is a strategic issue for almost every company. The problem of locating facilities and allocating customers covers the core topics of distribution system design. Model formulations and solution algorithms which address the issue vary widely in terms of fundamental assumptions, mathematical complexity and computational performance. This paper reviews some of the contributions to the current state-of-the-art. In particular, continuous location models, network location models, mixed-integer programming models, and applications are summarized.

© 2003 Elsevier B.V. All rights reserved.

Keywords: Strategic planning; Distribution system design; Facility location; Mixed-integer programming models

1. Introduction

Decisions about the distribution system are a strategic issue for almost every company. The problem of locating facilities and allocating customers covers the core components of distribution system design. Industrial firms must locate fabrication and assembly plants as well as warehouses. Stores have to be located by retail outlets. The ability to manufacture and market its products is dependent in part on the location of the facilities. Similarly, government agencies have to decide about the location of offices, schools, hospitals, fire stations, etc. In every case, the quality of the services depends on the location of the facilities in relation to other facilities.

The problem of locating facilities is not new to the operations research community; the challenge of where to best site facilities has inspired a rich, colorful and ever growing body of literature. To cope with the multitude of applications encountered in the business world and in the public sector, an ever expanding family of models has emerged. Location-allocation models cover formulations which range in complexity from simple linear, single-stage, single-product, uncapacitated, deterministic models to non-linear

* Corresponding author. Address: Institut für Operations Research, Universität Zürich, 8015 Zürich, Switzerland.
E-mail addresses: andreas.klose@unizg.ch (A. Klose), drexl@bwl.uni-kiel.de (A. Drexl).

probabilistic models. Algorithms include, among others, local search and mathematical programming-based approaches.

It is the purpose of this paper to review some of the work which has contributed to the current state-of-the-art. The focus is on the fundamental assumptions, mathematical models and specific references to solution approaches. For the sake of brevity, work which has been done using simulation is neglected (see, for instance, Connors et al., 1972).

The outline of the work is as follows: In Section 2 types of models are classified. Section 3 reviews continuous location models. Then, Section 4 is dedicated to network location models, while Section 5 provides mixed-integer programming models. Finally, Section 6 covers a variety of applications.

2. Types of models

Facility location models can be broadly classified as follows:

1. The shape or topography of the set of potential plants yields models in the plane, network location models, and discrete location or mixed-integer programming models, respectively. For each of the subclasses distances are calculated using some metric.
2. Objectives may be either of the minsum or the minmax type. Minsum models are designed to minimize average distances while minmax models have to minimize maximum distances. Predominantly, minsum models embrace location problems of private companies while minmax models focus on location problems arising in the public sector.
3. Models without capacity constraints do not restrict demand allocation. If capacity constraints for the potential sites have to be obeyed demand has to be allocated carefully. In the latter case we have to examine whether single-sourcing or multiple-sourcing is essential.
4. Single-stage models focus on distribution systems covering only one stage explicitly. In multi-stage models the flow of goods comprising several hierarchical stages has to be examined.
5. Single-product models are characterized by the fact that demand, cost and capacity for several products can be aggregated to a single homogeneous product. If products are inhomogeneous their effect on the design of the distribution system has to be analyzed, viz. multi-product models have to be studied.
6. Frequently, location models base on the assumption that demand is inelastic, that is, demand is independent of spatial decisions. If demand is elastic the relationship between, e.g., distance and demand has to be taken into account explicitly. In the latter case cost minimization has to be replaced through, for example, revenue maximization.
7. Static models try to optimize system performance for one representative period. By contrast dynamic models reflect data (cost, demand, capacities, etc.) varying over time within a given planning horizon.
8. In practice model input is usually not known with certainty. Data are based on forecasts and, hence, are likely to be uncertain. As a consequence, we have either deterministic models if input is (assumed to be) known with certainty or probabilistic models if input is subject to uncertainty.
9. In classical models the quality of demand allocation is measured on isolation for each pair of supply and demand points. Unfortunately, if demand is satisfied through delivery tours then, for instance, delivery cost cannot be calculated for each pair of supply and demand points separately. Combined location/routing models elaborate on this interrelationship.

Additional attributes such as single- vs. multiple-objective models or desirable vs. undesirable facilities may be distinguished (see, for instance, Aikens, 1985; Brandeau and Chiu, 1989; Daskin, 1995; ReVelle and Laporte, 1996; Hamacher and Nickel, 1998).

3. Continuous location models

Continuous location models (models in the plane) are characterized through two essential attributes: (a) The solution space is continuous, that is, it is feasible to locate facilities on every point in the plane. (b) Distance is measured with a suitable metric. Typically, the Manhattan or right-angle distance metric, the Euclidean or straight-line distance metric, or the l_p -distance metric is employed.

Continuous location models require to calculate coordinates $(x, y) \in \mathbb{R}^p \times \mathbb{R}^p$ for p facilities. The objective is to minimize the sum of distances between the facilities and m given demand points.

The subject of the Weber problem is to determine the coordinates $(x, y) \in \mathbb{R} \times \mathbb{R}$ of a single facility such that the sum of the (weighted) distances $w_k d_k(x, y)$ to given demand points $k \in K$ located in (a_k, b_k) is minimized. The corresponding optimization problem

$$v(\text{SWP}) = \min_{(x,y)} \sum_{k \in K} w_k d_k(x, y), \quad \text{where } d_k(x, y) = \sqrt{(x - a_k)^2 + (y - b_k)^2},$$

can be solved efficiently by means of an iterative procedure. This gradient-like search method was originally proposed by Weiszfeld (1937) and has been further improved by Miehle (1958). This simple problem has a century-long tradition for the case of $|K| = 3$ demand points and it has been included in the famous book of Weber (1909) giving the problem its nowadays name. The history of the Weber problem is well documented in Wesolowsky (1993).

An extended version of the problem requires to locate p , $1 < p < |K|$ facilities and to allocate demand to the chosen facilities. This problem, also denoted as multi-source Weber problem (MWP), is NP-hard. It can be modelled as the non-linear mixed-integer program

$$\begin{aligned} v(\text{MWP}) = \min & \sum_{k \in K} \sum_{j=1}^p (w_k d_k(x_j, y_j)) z_{kj}, \\ \text{s.t.} & \sum_{j=1}^p z_{kj} = 1 \quad \forall k \in K, \\ & z_{kj} \in \mathbb{B}, \quad \forall k \in K, \quad j = 1, \dots, p, \\ & x, y \in \mathbb{R}^p, \end{aligned}$$

where $\mathbb{B} = \{0, 1\}$ and z_{kj} equals 1 if demand point k is assigned to facility j . Exact solution procedures reformulate the model as a set partitioning problem, the LP-relaxation of which can be solved by column generation (see Rosing, 1992b; du Merle et al., 1999). Fast heuristic algorithms have been proposed by Taillard (1996), Hansen et al. (1998) and Brimberg et al. (2000). The special case of $p = 2$ facilities has been analyzed by Ostresh (1973), Drezner (1984), Rosing (1992b) and Chen et al. (1998).

A couple of variants and extensions of continuous location problems have been investigated in literature. To mention a few: Problems with barriers are the subject of, e.g., Hamacher and Nickel (1994), Käfer and Nickel (2001) and Klamroth (2001). The location of undesirable (obnoxious) facilities requires to maximize minimum distances (see, e.g., Melachrinoudis, 1988; Erkut and Neuman, 1989; Brimberg and Mehrez, 1994). Location models with both desirable and undesirable facilities have been analyzed in, for instance, Chen et al. (1992). Minmax location models have been dealt with, among others, by Krarup and Pruzan (1979), Love et al. (1988, p. 113 ff.) and Francis et al. (1992, p. 217 ff.).

4. Network location models

In network location models distances are computed as shortest paths in a graph. Nodes represent demand points and potential facility sites correspond to a subset of the nodes and to points on arcs.

The network location model corresponding to the continuous multi-source Weber model is called p -median problem. In the p -median problem p facilities have to be located on a graph such that the sum of distances between the nodes of the graph and the facility located nearest is minimized. Hakimi (1964, 1965) has shown that it is sufficient to restrict the set of potential sites to the set of nodes in the case of concave distance functions.

Let K denote the set of nodes, $J \subseteq K$ the set of potential facilities, $w_k d_{kj}$ the weighted distance between nodes k and j , y_j a binary decision variable being equal to 1 if node j is chosen as a facility (0, otherwise), and x_{kj} a binary decision variable reflecting the assignment of demand node $k \in K$ to the potential facility site j . Then

$$v(\text{PMP}) = \min \sum_{k \in K} \sum_{j \in J} (w_k d_{kj}) z_{kj}, \quad (1a)$$

$$\text{s.t. } \sum_{j \in J} z_{kj} = 1 \quad \forall k \in K, \quad (1b)$$

$$z_{kj} - y_j \leq 0 \quad \forall k \in K, j \in J, \quad (1c)$$

$$\sum_{j \in J} y_j = p, \quad (1d)$$

$$z_{kj}, y_j \in \mathbb{B} \quad \forall k \in K, \forall j \in J, \quad (1e)$$

formally describes the p -median problem. Constraints (1b) guarantee that demand is satisfied, inequalities (1c) couple the location and the assignment decision, and constraint (1d) fixes the number of selected facilities to p . Solution methods for the p -median problem have been presented by, e.g., Christofides and Beasley (1982), Hanjoul and Peeters (1985), Beasley (1993) and Klose (1993).

Let us now consider the p -center problem the aim of which is to locate p facilities such that the maximum distance is minimized. Unfortunately, for the p -center problem we cannot restrict the set of potential facility sites to the set of nodes because the maximum of concave distance functions is no concave function any more. Fortunately, it suffices to consider a finite set of points on the arcs. These points can be determined as intersection points q for which the weighted distance $w_i d_{iq}$ between q and node $i \in K$ equals the weighted distance $w_k d_{kq}$ between q and another node $k \in K$. Let J denote the set of intersection points. Then the discrete optimization model

$$v(\text{PCP}) = \min r, \quad (2a)$$

$$\text{s.t. } r - \sum_{j \in J} w_k d_{kj} z_{kj} \geq 0 \quad \forall k \in K, \quad (2b)$$

$$\sum_{j \in J} z_{kj} = 1 \quad \forall k \in K, \quad (2c)$$

$$z_{kj} - y_j \leq 0 \quad \forall k \in K, j \in J, \quad (2d)$$

$$\sum_{j \in J} y_j = p, \quad (2e)$$

$$z_{kj}, y_j \in \mathbb{B} \quad \forall k \in K, \forall j \in J, \quad (2f)$$

formally describes the p -center problem which can be transformed into a sequence of covering problems (see, e.g., Handler, 1979; Domschke and Drexl, 1996). We start with a given set $S \subseteq J$, $|S| \leq p$, of centers with radius $r = \max_{k \in K} \min_{j \in S} \{w_k d_{kj}\}$. Then the covering model

$$v(\text{SCP}) = \min \sum_{j \in J} y_j, \quad (3a)$$

$$\text{s.t.} \quad \sum_{j \in J} a_{kj} y_j \geq 1 \quad \forall k \in K, \quad (3b)$$

$$y_j \in \mathbb{B} \quad \forall j \in J, \quad (3c)$$

with $a_{kj} = 1$ for $w_k d_{kj} < r$ and $a_{kj} = 0$ for $w_k d_{kj} \geq r$ computes a set of at most p centers with a radius smaller than r or shows that no such set exists.

Recently, Boland et al. (2003) and Domínguez-Marín et al. (2003) considered the so-called “discrete ordered median problem” which contains, among others, p -median and p -center problems as special cases.

The models treated so far assume given demand and cost minimization as objective. On the contrary competitive facility location models aim at maximum sales or market shares. One of the first papers is due to Hotelling (1929). A survey and a classification can be found in Eiselt et al. (1993) (see also Dobson and Karmarkar, 1987; Bauer et al., 1993).

Given an undirected graph with arc and node weights two basic models can be described as follows. The nodes $k \in K$ of the graph represent the customers with known demand b_k for a certain product. Two companies A and B producing that product compete for customers. Company A (B) wants to locate r (p) facilities in order to satisfy customers. Originally none of the companies is present in the market. At first company A determines locations of r facilities, then company B does so for p facilities. Customers always choose the nearest facility; in case of ties demand is divided between A and B .

Let A_r (B_p) denote the set of facilities of A (B). Furthermore, let $v(B_p|A_r)$ denote the market share which can be achieved by company B choosing B_p , given A_r , then both companies have to solve two different problems (see Hakimi, 1983):

Given A_r , company B determines the set B_p^* such that $v(B_p^*|A_r) = \max_{B_p} \{v(B_p|A_r)\}$. If B_p can be chosen among all points of the graph we have to solve a $(p|A_r)$ -medianoid problem, if this choice is restricted to the set of nodes it is called maximum capture problem. Models and methods for both cases can be found in ReVelle (1986).

Company A determines, given B_p , the set A_r^* such that $v(A_r^*|B_p) = \max_{A_r} \{v(A_r|B_p)\}$. A_r either can be chosen among all points of the graph or is restricted to the set of nodes. The problem at hand is called $(p|r)$ -centroid problem. The reasoning is as follows: when A chooses his facilities no other facilities do already exist. A locates his facilities in such a way that the market share gained subsequently by B is minimized, i.e., A anticipates the reaction of his competitor. In fact A has to solve a minmax-problem, that is, he minimizes the maximum market share which can be gained subsequently by B .

$(p|A_r)$ -medianoid problems and $(p|r)$ -centroid problems are NP-hard if r and p are not fixed in advance. Given p the $(p|A_r)$ -medianoid problem can be solved in polynomial time if the choice is restricted to the node set (see Benati and Laporte, 1994).

5. Mixed-integer programming models

Starting with a given set of potential facility sites many location problems can be modelled as mixed-integer programming models. Apparently, network location models differ only gradually from mixed-integer programming models because the former ones can be stated as discrete optimization models. Yet network location models explicitly take the structure of the set of potential facilities and the distance metric into account while mixed-integer programming models just use input parameters without asking where they come from.

A rough classification of discrete facility location models can be given as follows: (a) single- vs. multi-stage models, (b) uncapacitated vs. capacitated models, (c) multiple- vs. single-sourcing, (d) single- vs. multi-product models, (e) static vs. dynamic models, and, last but not least, (f) models without and with routing options included.

5.1. Uncapacitated, single-stage models

The most simple model of this category solely considers the tradeoff between fixed operating and variable delivery cost. Mathematically,

$$v(\text{UFLP}) = \min \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} + \sum_{j \in J} f_j y_j, \quad (4a)$$

$$\text{s.t.} \quad \sum_{j \in J} z_{kj} = 1 \quad \forall k \in K, \quad (4b)$$

$$z_{kj} - y_j \leq 0 \quad \forall k \in K, j \in J, \quad (4c)$$

$$0 \leq z_{kj} \leq 1, \quad 0 \leq y_j \leq 1 \quad \forall k \in K, j \in J, \quad (4d)$$

$$y_j \in \mathbb{B} \quad \forall j \in J, \quad (4e)$$

describes the simple plant location problem (SPLP) or uncapacitated facility location problem (UFLP).

The UFLP can be formulated more compact by aggregating constraints (4c) to $\sum_{k \in K} z_{kj} \leq |K| y_j$. The LP-relaxation of this “weak” model can be solved analytically (see Efromson and Ray, 1966; Khumawala, 1972). Unfortunately, the lower bounds are very weak. Cornuejols and Thizy (1982) have shown that the restrictions (4b) and (4c) cover all clique cuts of the UFLP which accounts for the fact that the model (4) yields a tight LP-relaxation. Branch-and-bound algorithms for the UFLP based on dual ascent methods have been proposed by Erlenkotter (1978) and Körkel (1989). An enhanced branch-and-bound algorithm is presented in Goldengorin et al. (2003). Guignard (1988) considers the addition of Benders’ inequalities within a Lagrangean ascent method for the UFLP. Based on a rounding and filtering technique of Lin and Vitter (1992), Shmoys et al. (1997) develop a 3.16-approximation algorithm for the metric UFLP; Guha and Khuller (1998) and Chudak (1999) further improve this approximation bound to 2.4 and 1.74, respectively. Arora et al. (1998) give a polynomial-time approximation scheme for the special case of the Euclidean UFLP.

Obviously, the p -median problem (1) and the UFLP are close to each other. While the number of facilities is fixed in the p -median problem, the number of open depots is part of the UFLP solution. Both models can be combined if cardinality constraints,

$$p_L \leq \sum_{j \in J} y_j \leq p_U, \quad (5)$$

are added to (4). Usually the outcome is called account location problem or generalized p -median problem. The aggregate capacity constraint

$$\sum_{j \in J} s_j y_j \geq d(K), \quad (6)$$

where $s_j > 0$ denotes the maximum capacity of depot j and $d(K) = \sum_{k \in K} d_k$ total demand, ensures that facilities open in a feasible solution have enough capacity in order to satisfy demand. Adding constraint (6) to the UFLP,

$$v(\text{APLP}) = \min \left\{ \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} + \sum_{j \in J} f_j y_j : (4b)–(4e) \text{ and } (6) \right\}, \quad (7)$$

yields the aggregate capacity plant location problem (APLP). Exact algorithms for solving the APLP have been developed by Ryu and Guignard (1992b), Thizy (1994) and Klose (1998). The APLP is not important as a stand-alone model but it has a dominant role as a relaxation when solving models presented in Section 5.2.

The UFLP is closely related to covering problems (see Balas and Padberg, 1976). Formally the set covering problem (SCP) computes a minimal collection $\{M_j : j \in S\}$ of a family $\{M_j : j \in N\}$ of subsets of a set M such that $\bigcup_{j \in S} M_j = M$ holds. Letting $a_{kj} = 1$ for $k \in M_j$ and $a_{kj} = 0$ for $k \notin M_j$ translates it into model (3). The SCP is closely related to the set partitioning problem (SPaP)

$$v(\text{SPaP}) = \min \sum_{j \in J} y_j, \quad (8a)$$

$$\text{s.t. } \sum_{j \in J} a_{kj} y_j = 1 \quad \forall k \in K, \quad (8b)$$

$$y_j \in \mathbb{B} \quad \forall j \in J, \quad (8c)$$

and to the set packing problem (SPP):

$$v(\text{SPP}) = \max \sum_{j \in J} y_j, \quad (9a)$$

$$\text{s.t. } \sum_{j \in J} a_{kj} y_j \leq 1 \quad \forall k \in K, \quad (9b)$$

$$y_j \in \mathbb{B} \quad \forall j \in J. \quad (9c)$$

The covering model (3) itself is a location model: An optimal solution of (3) determines a minimal subset $S = \{j \in J : y_j = 1\}$ of facilities such that every customer can be reached within a given maximal distance from one of the chosen depots. An important variant of (3) is denoted as the maximum covering location problem (MCLP):

$$v(\text{MCLP}) = \max \sum_{k \in K} w_k z_k, \quad (10a)$$

$$\text{s.t. } \sum_{j \in J} a_{kj} y_j - z_k \geq 0 \quad \forall k \in K, \quad (10b)$$

$$\sum_{j \in J} y_j = p, \quad (10c)$$

$$z_k, y_j \in \mathbb{B} \quad \forall k \in K, j \in J. \quad (10d)$$

The MCLP requires to calculate a subset $S = \{j \in J : y_j = 1\}$ of facilities with cardinality p such that a maximum number of w_k weighted demand nodes $k \in K$ can be covered through facilities $j \in S$ within a given maximal distance (see, e.g., Schilling et al., 1993; Daskin, 1995; Galvão, 1996). Defining the parameters

$$c_{kj} = \begin{cases} 0 & \text{for } a_{kj} = 1, \\ \infty & \text{for } a_{kj} = 0, \end{cases} \text{ and } f_j = 1 \quad \forall j \in J,$$

states the SCP (3) as an UFLP. Additionally, because of

$$\begin{aligned} v(\text{MCLP}) &= \max \left\{ \sum_{k \in K} \sum_{j \in J} a_{kj} w_k z_{kj} : (1b)-(1e) \right\} \\ &= \sum_{k \in K} w_k - \min \left\{ \sum_{k \in K} \sum_{j \in J} (1 - a_{kj}) w_k z_{kj} : (1b)-(1e) \right\}, \end{aligned}$$

the MCLP (10) is equivalent to the p -median problem with the special “distance” measure $d_{kj} = (1 - a_{kj})w_k$. On the contrary substituting variables y_j in the UFLP through their complement $y_j^c = 1 - y_j$ and adding slack variables r_{kj} in (4c) leads to the special SPaP

$$\begin{aligned} \min \quad & \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} - \sum_{j \in J} f_j y_j^c + \sum_{j \in J} f_j, \\ \text{s.t.} \quad & \sum_{j \in J} z_{kj} = 1 \quad \forall k \in K, \\ & z_{kj} + y_j^c + r_{kj} = 1 \quad \forall k \in K, j \in J, \\ & z_{kj}, r_{kj}, y_j^c \in \mathbb{B} \quad \forall k \in K, j \in J, \end{aligned}$$

which in turn can be transformed into the SPP

$$\begin{aligned} \max \quad & \sum_{k \in K} \sum_{j \in J} (L_k - c_{kj}) z_{kj} + \sum_{j \in J} f_j y_j^c - \sum_{k \in K} L_k - \sum_{j \in J} f_j, \\ \text{s.t.} \quad & \sum_{j \in J} z_{kj} \leq 1 \quad \forall k \in K, \\ & z_{kj} + y_j^c \leq 1 \quad \forall k \in K, j \in J, \\ & z_{kj}, y_j^c \in \mathbb{B} \quad \forall k \in K, j \in J, \end{aligned}$$

by replacing min through max and penalizing the slack $\sum_j z_{kj} - 1$ with a sufficiently large L_k . Guignard (1980), Cho et al. (1983) and Cornuejols and Thizy (1982) capitalize on the transformation from UFLP to SPaP and SPP in order to study the polyedral structure of the UFLP. These relationships date back to Krarup and Pruzan (1983).

The UFLP can be transformed into the SCP as follows: Replace in (8) the restrictions $\sum_j a_{kj} y_j = 1$ through inequalities $\sum_j a_{kj} y_j \geq 1$ and gather the slack variables $\sum_j a_{kj} y_j - 1$ with sufficiently large penalties L_k in the objective function.

5.2. Capacitated, single-stage models

If depots have scarce capacity, constraints

$$\sum_{k \in K} d_k z_{kj} \leq s_j y_j \quad \forall j \in J, \tag{11}$$

limiting transshipments $\sum_k d_k z_{kj}$ for the depots selected ($y_j = 1$) to their capacity s_j have to be added. Hence, in the case of scarce capacity the UFLP mutates to the capacitated facility location problem (CFLP). Furthermore, uncapacitated facility location problems with increasing unit cost of throughput can be modeled as mixed-integer programs, which closely resemble the structure of the CFLP (see Harkness and ReVelle, 2003).

The extended formulation

$$\begin{aligned}
 v(\text{CFLP}) &= \min \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} + \sum_{j \in J} f_j y_j, \\
 \text{s.t.} \quad & \sum_{j \in J} z_{kj} = 1 \quad \forall k \in K, & \text{(D)} \\
 & \sum_{k \in K} d_k z_{kj} - s_j y_j \leq 0 \quad \forall j \in J, & \text{(C)} \\
 & z_{kj} - y_j \leq 0 \quad \forall k \in K, \quad \forall j \in J, & \text{(B)} \\
 & \sum_{j \in J} s_j y_j \geq d(K), & \text{(T)} \\
 & \sum_{j \in J_q} z_{kj} \leq 1 \quad \forall k \in K, \quad \forall q \in Q, & \text{(U)} \\
 & 0 \leq z_{kj} \leq 1, \quad 0 \leq y_j \leq 1 \quad \forall k \in K, \quad \forall j \in J, & \text{(N)} \\
 & y_j \in \{0, 1\} \quad \forall j \in J, & \text{(I)}
 \end{aligned}$$

of the CFLP is a nice starting point in order to study various relaxations. A common way to obtain lower bounds for the CFLP is to relax constraints (C) and/or (D) in a Lagrangean manner and to add some additional inequalities which are implied by the relaxed constraints and some of the other constraints. The valid inequalities which are usually considered for these purposes are the variable upper bound or trivial clique constraints (B) and the aggregate capacity constraint (T). Besides the two additional constraints (B) and (T), one may devise a number of valid inequalities which can be useful to sharpen a relaxation, provided that the resulting subproblem is manageable. One group of redundant constraints is easily constructed as follows. Let $\{J_q : q \in Q\}$, $J_q \cap J_h = \emptyset \quad \forall q \neq h$, denote a given partitioning of the set J of potential plant locations. Then the ‘‘clique constraints’’ (U) are implied by (D); however, they can be useful if constraints (D) are relaxed.

Without taking constraints (U) into account, Cornuejols et al. (1991) examine all possible ways of applying Lagrangean relaxation/decomposition to the CFLP. Following their notation:

- let Z_R^S denote the resulting lower bound if constraint set S is ignored and constraints R are relaxed in a Lagrangean fashion, and
- let Z_{R_1/R_2} denote the bound which results if Lagrangean decomposition is applied in such a way that constraints R_1 and R_2 are split into two subproblems.

Regarding Lagrangean relaxation, Cornuejols et al. (1991, Theorem 1) show that

$$Z^{\text{BIU}} \leq Z^{\text{IU}} \leq Z_C^{\text{TU}} \leq Z_C^{\text{U}} \leq Z, \quad Z^{\text{IU}} \leq Z_D^{\text{U}} \leq Z_C^{\text{U}}, \quad \text{and} \quad Z^{\text{BIU}} \leq Z_C^{\text{BU}} \leq Z_D^{\text{U}}.$$

Furthermore, they provide instances showing that all the inequalities above can be strict. The subproblem corresponding to Z_D^{U} can be converted to a knapsack problem and is solvable in pseudo-polynomial time. Therefore, bounds inferior to Z_D^{U} seem not to be interesting. Furthermore, as computational experiments show, $Z_C^{\text{TU}} = Z_C^{\text{T}}$ is usually not stronger than Z_D^{U} . This leaves Z_D^{U} and $Z_C^{\text{U}} = Z_C$ as candidate bounds. Since constraints (U) are implied by (D), constraints (U) can only be helpful if constraints (D) are relaxed. If the aggregate capacity constraint (T) is relaxed as well, the resulting Lagrangean subproblem decomposes into $|Q|$ smaller CFLPs. Obviously,

$$Z_D^{\text{T}} = \begin{cases} Z_D^{\text{TU}} = Z_{\text{DU}}^{\text{T}} = Z^{\text{IU}} = Z^{\text{T}} & \text{if } |Q| = |J|, \\ Z & \text{if } |Q| = 1. \end{cases}$$

For $1 < |Q| < |J|$, however, the bound Z_D^T can be anywhere between the (strong) LP-bound $Z^{IU} = Z^I$ and the optimum value Z of the CFLP, i.e., $Z^I \leq Z_D^T \leq Z$. Although the subproblem corresponding to Z_D^T has the same structure as the CFLP, the bound Z_D^T may be advantageous, if the set of potential plant locations is large and if the capacity constraints are not very tight.

With respect to Lagrangean decomposition, Cornuejols et al. (1991, Theorem 2) proof that

$$\begin{aligned} Z_{C/D}^U &= Z_{C/DB}^U = Z_{C/DT}^U = Z_{C/DBT}^U = Z_C^U, & \max\{Z_C^{TU}, Z_D^U\} &\leq Z_{D/TC}^U \leq Z_C^U & \text{ and } & Z_{D/BC}^U = Z_{D/TBC}^U \\ &= Z_{TD/BC}^U = Z_D^U. \end{aligned}$$

Since Lagrangean decomposition requires to solve two subproblems in each iteration and to optimize a large number of multipliers, Lagrangean decomposition should give a bound which is at least as strong as Z_D^U . The only remaining interesting bound is, therefore, $Z_{D/TC}^U$. As shown by Chen and Guignard (1998), the bound $Z_{D/TC}^U$ is also obtainable by means of a technique called Lagrangean substitution, which substitutes the copy constraints $x = x'$ by $\sum_k d_k z_{kj} = \sum_k d_k x'_{kj}$. Compared to the Lagrangean decomposition, this reduces the number of dual variables from $|K| \cdot |J| + |J|$ to $2|J|$.

In summary, interesting Lagrangean bounds for the CFLP are Z_D^U , Z_C , $Z_{D/TC}^U$ and Z_D^T . Compared to Z_C , the computation of the bound $Z_{D/TC}^U$ requires to optimize an increased number of dual variables. Furthermore, one of the subproblems corresponding to $Z_{D/TC}^U$ is an UFLP while the subproblem corresponding to Z_C is an APLP. Since the bound $Z_{D/TC}^U$ is no stronger than Z_C and since an APLP is often not much harder to solve than an UFLP, the bound $Z_{D/TC}^U$ can be discarded. The computation of these bounds by means of column generation is described in detail in Klose and Drexl (2001).

In the CFLP demand d_k can be supplied from more than one depot. Given a certain set of depots the CFLP reduces to a simple transportation problem. Apparently, this implies transportation cost being proportional to shipment volumes. In many practical settings this assumption does not hold and, moreover, it is required that each customer is satisfied from exactly one depot. In this case additional constraints

$$z_{kj} \in \mathbb{B} \quad \forall k \in K, j \in J, \tag{12}$$

yield a pure integer program, well-known as capacitated facility location problem with single sourcing (CFLPSS). Unfortunately, single sourcing constraints make the problem much harder to solve. For a given set O of open depots an optimal solution of the NP-hard generalized assignment problem (GAP)

$$v(\text{GAP}) = \min \sum_{k \in K} \sum_{j \in O} c_{kj} z_{kj}, \tag{13a}$$

$$\text{s.t. } \sum_{j \in O} z_{kj} = 1 \quad \forall k \in K, \tag{13b}$$

$$\sum_{k \in K} d_k z_{kj} \leq s_j \quad \forall j \in O, \tag{13c}$$

$$z_{kj} \in \mathbb{B} \quad \forall k \in K, j \in O, \tag{13d}$$

provides a minimum cost assignment of customers to depots. Note that the GAP usually is formulated in such a way that capacity requirements depend on the assignments also (see Martello and Toth, 1990, p. 189 ff.).

Without surprise it is very difficult to calculate an exact solution for instances of realistic size. From an algorithmic point of view, both for the CFLP and the CFLPSS, Lagrangean relaxation (dual decomposition) plays a dominant role (see Geoffrion and McBride, 1978; Nauss, 1978; Christofides and Beasley, 1983; Guignard and Kim, 1983; Barcelo and Casanovas, 1984; Klinecicz and Luss, 1986; Beasley, 1988, 1993; Shetty, 1990; Barcelo et al., 1990; Cornuejols et al., 1991; Ryu and Guignard, 1992a; Sridharan, 1993, 1995; Holmberg et al., 1999; Díaz, 2001; Díaz and Fernandez, 2001), additionally, primal and pri-

mal-dual decomposition algorithms have been developed (see Van Roy, 1986; Wentges, 1994, 1996). In the framework of tabu search it is shown in Grünert (2002) for the CFLP how promising neighbors can be identified by means of Lagrangean relaxation. Approximation algorithms for the CFLP are considered in Shmoys et al. (1997), Guha and Khuller (1998), Korupolu et al. (1998), Chudak and Williamson (1999) and Chudak and Shmoys (1999); Delmaire et al. (1999) employ a GRASP as well as a tabu search procedure for the CFLPSS; Scaparra (2002) proposes local search procedures based on exponentially sized “cyclic transfer” neighborhoods for this problem, and a number of metaheuristic approaches (evolutionary algorithm, simulated annealing, GRASP, tabu search) to the CFLPSS are discussed in Díaz (2001).

5.3. Multi-stage models

Consider a distribution system consisting of facilities on several hierarchically layered levels. Facility locations on a higher level can be determined independently of the chosen locations on a lower level if the following conditions are met: higher level nodes have a sufficiently high capacity and handling costs as well as transshipment costs associated with these nodes are proportional to the amount of items reloaded and shipped, respectively. Transshipment cost from the source to the depot then can be charged proportional to the cost of allocated demand. Otherwise transshipments covering several stages of the distribution system have to be considered explicitly. Clearly, multi-stage facility location problems are present if depots have to be located simultaneously on several layers of the distribution system.

The CFLP and the CFLPSS have to be generalized to a two-stage capacitated facility location model if the flow of products from a capacity-constrained predecessor stage (e.g., production facility, central distribution facility) to the potential depots is an additional decision variable. Let x_{ij} denote the amount which has to be shipped from predecessor node $i \in I$ having capacity p_i to a depot located in node j . Furthermore, let t_{ij} denote the transshipment cost per unit (containing the handling cost at node i also) then the following two-stage capacitated facility location problem (TSCFLP) arises:

$$v(\text{TSCFLP}) = \min \sum_{i \in I} \sum_{j \in J} t_{ij} x_{ij} + \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} + \sum_{j \in J} f_j y_j, \quad (14a)$$

$$\text{s.t. (4b)–(4e), (6) and (11),}$$

$$\sum_{j \in J} x_{ij} \leq p_i \quad \forall i \in I, \quad (14b)$$

$$\sum_{i \in I} x_{ij} = \sum_{k \in K} d_k z_{kj} \quad \forall j \in J, \quad (14c)$$

$$x_{ij} - p_i y_j \leq 0 \quad \forall i \in I, j \in J, \quad (14d)$$

$$x_{ij} \geq 0 \quad \forall i \in I, j \in J. \quad (14e)$$

If single-sourcing of demand nodes is required constraints (12) have to be added. Constraints (14b) take care of limited capacities at higher level nodes while restrictions (14c) are flow conservation constraints. (14d) are redundant but useful in order to tighten some relaxations. If the capacity p_i of each node $i \in I$ is sufficiently large in order to cover the total demand $d(K)$ per period then the TSCFLP reduces to the CFLP or the CFLPSS, respectively.

If we introduce variables w_{ijk} which denote the fraction of demand d_k being routed via path $i \rightarrow j \rightarrow k$ then an alternative TSCFLP model can be stated as follows for the case of single sourcing:

$$\begin{aligned}
 v(\text{TSCFLP}) = \min & \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} q_{ijk} w_{ijk} + \sum_{j \in J} f_j y_j, \\
 \text{s.t. } & (4b)–(4e), (6) (11) \text{ and } (12), \\
 & \sum_{i \in I} w_{ijk} = z_{kj} \quad \forall j \in J, k \in K, \\
 & \sum_{j \in J} \sum_{k \in K} d_k w_{ijk} \leq p_i \quad \forall i \in I, \\
 & \sum_{k \in K} d_k w_{ijk} \leq p_i y_j \quad \forall i \in I, j \in J, \\
 & w_{ijk} \geq 0 \quad \forall i \in I, j \in J, k \in K.
 \end{aligned}$$

In this model $q_{ijk} = t_{ij}d_k + c_{kj}$ defines the procurement cost of node $k \in K$ via path $i \rightarrow j \rightarrow k$. Note that this formulation allows to model situations where the cost depend on both the source node i and the sink node k . Such cases occur in practice if for instance freight rates from source i to depot j are less than the sum of freight rates from i to j plus j to k . Apparently, the first model is advantageous if the cost q_{ijk} can be split into two parts $t_{ij}d_k$ and c_{kj} , because it has far fewer decision variables while the values of the LP-relaxations of both models are identical.

If demand splitting is allowed then the variables z_{kj} can be eliminated in the second model. Accordingly, the demand constraint can be rewritten as $\sum_{i \in I} \sum_{j \in J} w_{ijk} = 1$ and the depot capacity restrictions as $\sum_{i \in I} \sum_{k \in K} d_k w_{ijk} \leq s_j y_j$.

In general, models where facilities on several stages of a distribution system have to be located are called multi-level hierarchical facility location problems. In contrast to the TSCFLP the tightness of relaxations depends on whether variables for single links or variables covering whole paths of the network are used. If g_i denotes the fixed cost of facility $i \in I$ on the highest level and γ_i corresponding decision variables then the TSCFLP generalizes to the following two-level capacitated facility location problem (TLCFLP):

$$\begin{aligned}
 v(\text{TLCFLP}) = \min & \sum_{i \in I} \sum_{j \in J} t_{ij} x_{ij} + \sum_{k \in K} \sum_{j \in J} c_{kj} z_{kj} + \sum_{i \in I} g_i \gamma_i + \sum_{j \in J} f_j y_j, \\
 \text{s.t. } & (4b)–(4e), (6), (11), (14c) \text{ and } (14e), \\
 & \sum_{j \in J} x_{ij} \leq p_i \gamma_i \quad \forall i \in I, \\
 & x_{ij} - \min\{p_i, s_j\} \gamma_i \leq 0 \quad \forall i \in I, j \in J, \\
 & \sum_{i \in I} p_i \gamma_i \geq d(K), \\
 & \gamma_i \in \mathbb{B} \quad \forall i \in I.
 \end{aligned}$$

Analogously, the UFLP generalizes to the two-level uncapacitated facility location problem (TUFLP). An equivalent formulation of the TLCFLP based on path variables w_{ijk} can be given as follows:

$$v(\text{TLCFLP}) = \min \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} q_{ijk} w_{ijk} + \sum_{i \in I} g_i \gamma_i + \sum_{j \in J} f_j y_j, \quad (15a)$$

$$\text{s.t.} \quad \sum_{i \in I} \sum_{j \in J} w_{ijk} = 1 \quad \forall k \in K, \quad (15b)$$

$$\sum_{j \in J} \sum_{k \in K} d_k w_{ijk} \leq p_i \gamma_i \quad \forall i \in I, \quad (15c)$$

$$\sum_{i \in I} \sum_{k \in K} d_k w_{ijk} \leq s_j y_j \quad \forall j \in J, \quad (15d)$$

$$\sum_{j \in J} w_{ijk} \leq \gamma_i \quad \forall i \in I, k \in K, \quad (15e)$$

$$\sum_{i \in I} w_{ijk} \leq y_j \quad \forall j \in J, k \in K, \quad (15f)$$

$$\sum_{j \in J} s_j y_j \geq d(K), \quad (15g)$$

$$\sum_{i \in I} p_i \gamma_i \geq d(K), \quad (15h)$$

$$w_{ijk} \geq 0 \quad \forall i \in I, j \in J, k \in K, \quad (15i)$$

$$\gamma_i, y_j \in \mathbb{B} \quad \forall i \in I, j \in J. \quad (15j)$$

Constraints (15b) guarantee that demand is satisfied completely. Constraints (15c) and (15d) take care of scarce capacities of facilities on both levels. Aggregate capacity constraints (15g) and (15h) are redundant but probably useful in order to tighten relaxations. The left hand side of (15f) corresponds to the variable z_{kj} in the former TLCFLP model and, hence, (15f) is equivalent to (4c). However, the left hand side of (15e) covers the fraction of demand d_k being shipped to $k \in K$ indirectly from $i \in I$. Note that this term cannot be incorporated in the former model because the flows on the two stages are modelled independently.

The pros and cons of two-level hierarchical facility location models based on path variables are discussed in Tcha and Lee (1984), Barros and Labbé (1992), Gao and Robinson Jr. (1992, 1994), Aardal et al. (1996), Barros (1998) and Aardal (1998).

Two- or multi-level facility location models cover complete distribution systems. In particular, if such models comprise the production stage also integrated production distribution planning—or strategic supply chain management—is the topic (see, e.g., Chandra and Fisher, 1994; Pooley, 1994; Vidal and Goetschalckx, 1997; Erengüç et al., 1999; Goetschalckx et al., 2002). Two-level (hierarchical) capacitated facility location models can be found in Geoffrion and Graves (1974), Hindi and Basta (1994), Hindi et al. (1998), Pirkul and Jayaraman (1996, 1998), Tragantalerngsak et al. (1997), Aardal (1998), Chardaire (1999), Marín and Pelegrín (1999) and Klose (1999, 2000); uncapacitated, hierarchical facility location models are discussed in Tcha and Lee (1984), Barros and Labbé (1992), Barros (1998), Gao and Robinson Jr. (1992, 1994), Aardal et al. (1996), Chardaire (1999) and Chardaire et al. (1999).

5.4. Multi-product models

The models discussed so far are based on aggregated demand, production, handling as well as distribution cost. Furthermore, capacity of production, depot and transshipment nodes must be given uniquely for all the products. Such an aggregation is no more valid if different products make different claims on the capacities of some nodes of the network. In this case we must proceed to a multi-product model, where, for instance, the capacities of nodes, the demand as well as the flows are separated with respect to some homogeneous product groups. Such multi-product variants of the TSCFLP and TLCFLP have been presented in Geoffrion and Graves (1974), Hindi and Basta (1994), Hindi et al. (1998) and Pirkul and Jayaraman (1996, 1998).

Other types of multi-product models arise, e.g., if (a) different types of facilities have to be distinguished at some locations and/or if (b) fixed cost of locations depend on the product provided by a location. The first type is called “multi-type model” by Karkazis and Boffey (1981), Boffey and Karkazis (1984), Mirchandani et al. (1985), Lee (1996) and Mazzola and Neebe (1999) and the second is called “multi-activity model” by Klineciewicz et al. (1986), Barros and Labbé (1992), Gao and Robinson Jr. (1992, 1994) and Barros (1998). Both can be modelled uniquely if different types of facilities correspond to different products. Fixed cost depend on products if a specific infrastructure or equipment is required in order to provide a product or service at a specific location.

Let I denote the set of product families $i \in I$ and (in addition to the fixed cost f_j) g_{ij} the fixed product cost. Then an uncapacitated multi-activity model, also called multi-commodity or multi-activity uncapacitated facility location problem (MUFLP) can be given as follows:

$$v(\text{MUFLP}) = \min \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} q_{ijk} w_{ijk} + \sum_{i \in I} \sum_{j \in J} g_{ij} z_{ij} + \sum_{j \in J} f_j y_j, \tag{16a}$$

$$\text{s.t.} \quad \sum_{j \in J} w_{ijk} = 1 \quad \forall i \in I, k \in K, \tag{16b}$$

$$z_{ij} - y_j \leq 0 \quad \forall i \in I, j \in J, \tag{16c}$$

$$w_{ijk} - z_{ij} \leq 0 \quad \forall i \in I, j \in J, k \in K, \tag{16d}$$

$$z_{ij}, y_j \in \mathbb{B} \quad \forall i \in I, j \in J, \tag{16e}$$

$$w_{ijk} \geq 0 \quad \forall i \in I, j \in J, k \in K. \tag{16f}$$

Here, z_{ij} is a binary variable which equals 1 if product/service type i is provided at depot j . The variable w_{ijk} denotes the fraction of demand d_{ik} of demand node k for product i which is covered by depot j . Likewise q_{ijk} denotes the cost of providing d_{ik} units of product i from depot j to demand node $k \in K$. Constraints (16b) require that the demand of each customer is covered. The coupling constraints (16c) and (16d) forbid to assign products to closed depots and to deliver product i to node k from depot j if product i is unavailable at the depot. In the multi-type case each facility can provide one product or service and, hence, the constraints

$$\sum_{i \in I} z_{ij} \leq 1 \quad \forall j \in J,$$

have to be added.

The model MUFLP adds product depot allocation decisions to the UFLP. Gao and Robinson Jr. (1992, 1994) show that the MUFLP is a special two-stage hierarchical facility location model. To this end products $i \in I$ have to be viewed as locations on the higher level and customer-product pairs (k, i) as single customers $k' \in K' = K \times I$ which have to be satisfied from combined locations (i, j) . Allocation cost $q_{ijk'}$ are prohibitive large if k' does not correspond to product type i . The resulting formulation

$$\begin{aligned}
 v(\text{MUFLP}) &= \min \sum_{i \in I} \sum_{j \in J} \sum_{k \in K'} q_{ijk} w_{ijk'} + \sum_{i \in I} \sum_{j \in J} g_{ij} z_{ij} + \sum_{j \in J} f_j y_j, \\
 \text{s.t.} \quad & \sum_{i \in I} \sum_{j \in J} w_{ijk'} = 1 \quad \forall k \in K', \\
 & z_{ij} - y_j \leq 0 \quad \forall i \in I, j \in J, \\
 & w_{ijk'} - z_{ij} \leq 0 \quad \forall i \in I, j \in J, k \in K', \\
 & z_{ij}, y_j \in \mathbb{B} \quad \forall i \in I, j \in J, \\
 & w_{ijk} \geq 0 \quad \forall i \in I, j \in J, k \in K',
 \end{aligned}$$

is a two-stage hierarchical facility location model in which the fixed cost g_{ij} of lower level location $j \in J$ are determined completely through the assignment to a location $i \in I$ at the higher level.

5.5. Dynamic models

In general, decisions about facility locations are made on a long-term basis. Depots, distribution centers and transshipment points once established shall be used for a couple of periods. However, factors influencing such decisions vary over time. In particular, demand (volume, regional distribution) and cost structures may change, but relocation and/or redimensioning of facilities can be quite costly. In order to cope with such issues dynamic location and allocation models have been developed. Dynamic location models are provided, for instance, by Schilling (1980), Erlenkotter (1981), Van Roy and Erlenkotter (1982), Frantzeskakis and Watson-Gandy (1989) and Shulman (1991).

In a dynamic version of the UFLP for every depot a close or open option is available in every period $t = 1, \dots, T$ where T denotes a given planning horizon. Fixed cost g_{ij}^c and g_{ij}^o for closing and opening depots are added to the fixed depot operating cost f_{ij} for relocation purposes. Closing cost g_{ij}^c have to be paid if depot $j \in J$ which is open in period $t - 1$, that is, $y_{t-1,j} = 1$, is closed in period t , i.e., $y_{t,j} = 0$; on the contrary opening cost g_{ij}^o result if a depot which is closed in period $t - 1$, that is, $y_{t-1,j} = 0$, is opened in period t , i.e., $y_{t,j} = 1$. The following quadratic integer program is a dynamic version DUFLP of UFLP:

$$\begin{aligned}
 v(\text{DUFLP}) &= \min \sum_{t=1}^T \sum_{k \in K} \sum_{j \in J} c_{tkj} z_{tkj} + \sum_{t=1}^T \sum_{j \in J} f_{tj} y_{tj} + \sum_{t=1}^T \left(\sum_{j \in J} g_{ij}^c y_{t-1,j} (1 - y_{tj}) + \sum_{j \in J} g_{ij}^o (1 - y_{t-1,j}) y_{tj} \right), \\
 \text{s.t.} \quad & \sum_{j \in J} z_{tkj} = 1 \quad \forall k \in K, t = 1, \dots, T, \\
 & z_{tkj} - y_{tj} \leq 0 \quad \forall k \in K, \forall j \in J, t = 1, \dots, T, \\
 & z_{tkj}, y_{tj} \in \mathbb{B} \quad \forall k \in K, \forall j \in J, t = 1, \dots, T.
 \end{aligned}$$

DUFLP can be linearized by introducing the binary variables $u_{t-1,t,j} \equiv y_{t-1,j} y_{tj}$ and the additional constraints

$$u_{t-1,t,j} \leq y_{t-1,j}, \quad u_{t-1,t,j} \leq y_{tj}, \quad u_{t-1,t,j} \geq y_{t-1,j} + y_{tj} - 1.$$

Supplementary constraints

$$y_{t+\tau_1,j} \geq y_{tj} \text{ for } \tau = 1, \dots, \tau_1 \quad \text{or} \quad y_{t+\tau_0,j} \leq y_{tj} \text{ for } \tau = 1, \dots, \tau_0,$$

achieve that the status of a depot opened (closed) in period t remains open (close) for at least τ_1 (τ_0) periods. The dynamic UFLP variant of Van Roy and Erlenkotter (1982) further boils down opening/closing options. Closing a depot $j \in J_1$ being originally open is feasible in one period t only. Similarly, opening a depot $j \in J_0$ being originally closed is feasible in one period t only. Let the binary variable y_{tj} equal 1 (0) if a depot

$j \in J_1$ ($j \in J_0$) is closed (opened). Furthermore, let F_{tj} denote the discounted cash flow of the period fixed cost for the periods $1, \dots, t$ for $j \in J_1$ and for the periods t, \dots, T for $j \in J_0$. Then we get the following “simplified” dynamic version of the UFLP:

$$\min \sum_{t=1}^T \left(\sum_{k \in K} \sum_{j \in J} c_{tkj} z_{tkj} + \sum_{j \in J} F_{tj} y_{tj} \right), \quad (17a)$$

$$\text{s.t. } \sum_{j \in J} z_{tkj} = 1 \quad \forall k \in K, \quad t = 1, \dots, T, \quad (17b)$$

$$z_{tkj} \leq \sum_{\tau=1}^t y_{\tau j} \quad \forall k \in K, \quad j \in J_0, \quad t = 1, \dots, T, \quad (17c)$$

$$z_{tkj} \leq \sum_{\tau=t}^T y_{\tau j} \quad \forall k \in K, \quad j \in J_1, \quad t = 1, \dots, T, \quad (17d)$$

$$z_{tkj}, y_{tj} \in \mathbb{B} \quad \forall k \in K, \quad j \in J, \quad t = 1, \dots, T. \quad (17e)$$

Constraints (17c) achieve that demand nodes $k \in K$ can be assigned to locations $j \in J_0$ in period t if the depot has been opened in period $\tau \leq t$. Likewise constraints (17d) prevent that demand nodes $k \in K$ are assigned to locations $j \in J_1$ in periods $t \geq \tau$ if the depot will be closed in period τ . Note that demand allocation can be changed in every period while opening/closing of a depot is possible only once.

Dynamic models seem to be adequate in light of factors changing over time. However, their practical relevance seems to be limited. First, a “right” planning horizon does not exist. Second, the amount of data required is enormous. Third, “disaggregated” models are more sensitive to parameter/data adjustments than aggregated ones. Fourth, the complexity of dynamic models increases—compared with static models—dramatically and, hence, the chances to solve such models decrease.

5.6. Probabilistic models

In practice some of the input data of location models are subject to uncertainty. Berman and Larson (1985), for instance, analyze queuing location models. Given certain distribution functions for the customer arrival process, waiting and service times are approximated. The waiting times are a function of the demand allocation and, hence, of facility location.

A stochastic variant of the p -median problem is discussed in Mirchandani et al. (1985). In particular, the input data demand and arc weights are supposed to be random variables. Under certain assumptions a finite number of states $i \in I$ of the graph with known probabilities can be enumerated. The objective of the model (18) is to minimize the expected sum of the weighted distances:

$$\min \sum_{i \in I} \sum_{k \in K} \sum_{j \in J} \pi_i c_{ikj} z_{ikj}, \quad (18a)$$

$$\text{s.t. } \sum_{j \in J} z_{ikj} = 1 \quad \forall i \in I, \quad j \in J, \quad (18b)$$

$$z_{ikj} - y_j \leq 0 \quad \forall i \in I, \quad k \in K, \quad j \in J, \quad (18c)$$

$$\sum_{j \in J} y_j = p, \quad (18d)$$

$$z_{ikj}, y_j \in \mathbb{B} \quad \forall i \in I, \quad k \in K, \quad j \in J. \quad (18e)$$

The symbol c_{ikj} denotes the demand weighted distance between nodes $k \in K$ and $j \in J$ in state $i \in I$. The decision variables z_{ikj} take care of the demand allocation in state $i \in I$, the variables y_j model the location

decisions. The stochastic p -median model (18) can easily be reduced to (1) by replacing the variables z_{ikj} through variables z_{lj} , $l = k + |I|(i - 1)$, denoting the assignment of demand node $k \in K$ in state $i \in I$ with corresponding allocation cost $c_{lj} = \pi_i c_{ikj}$. Similarly, stochastic variants of the UFLP and CFLP can be considered, but in the case of the CFLP capacity constraints prevent the reduction to a deterministic CFLP with an increased number of demand nodes. Further stochastic location models are, e.g., discussed in Laporte et al. (1994) and Listes and Dekker (2001). Laporte et al. (1994) develop a branch-and-cut algorithm for a location problem with stochastic demand; Listes and Dekker (2001) use stochastic models with recourse for the purposes of locating facilities in product recovery networks.

Unfortunately, stochastic models require a large amount of data in order to adapt empirically observed distributions to theoretical ones. Usually for strategic facility location problems such information is not available. Probably, calculating solutions, supported by sensitivity analysis, for some scenarios is useful. To gain insight into the effects of parameter changes is important. Furthermore, scenario analysis can be employed. This approach tries to find solutions which perform best over a set of scenarios with respect to some kind of regret measure (see, e.g., Owen and Daskin, 1998; Barros et al., 1998).

5.7. Hub location models

Recently, hub location models have received considerable attention. Usually, they are studied on hub-and-spoke networks with the following properties: For an undirected graph with node set K a flow exists between every pair $i, j \in K$ of nodes. A subset of “central” nodes act as transshipment nodes (hubs); the other (terminal or non-hub) nodes are connected with an arc (spoke) starlike with one of the hubs. Flows from one node to another node travel directly if both nodes are hub nodes or if one node is a hub node and both are connected through a spoke. Otherwise, flow travels via at least another hub node.

Similar to p -median and facility location models the number of hubs can be fixed or subject to decision, capacities can be scarce or non-scarce. Additionally, the hub nodes can constitute a complete graph, a tree or a graph without special characteristics. The non-hub (terminal) nodes are linked via arcs with hub nodes (and probably with other non-hub nodes also). If each terminal node has to be connected with exactly one hub node the single allocation case is given. Otherwise, if terminal nodes have access to more than one hub the multiple allocation hub location problem arises.

In what follows we consider a multiple allocation hub location problem in more detail. Assume an undirected, complete graph with $n = |K|$ nodes, arc set E and arc weights c . For each pair of nodes i and j the volume of traffic (flow) equals v_{ij} . Each node $k \in H$ of a subset $H \subseteq K$ of nodes can be chosen as hub node. The fixed cost of locating a hub in node $k \in H$ equal f_k . The hub network is a complete subgraph. Flows between terminal nodes travel via at most two hubs, flows between terminal nodes are infeasible. c_{kj} denotes the arc weights (cost per unit). If one unit travels from terminal node i via hub nodes k and m to terminal node j then the cost are $c_{ikmj} = c_{ik} + \alpha \cdot c_{km} + c_{mj}$; α is scaling factor, $0 < \alpha \leq 1$. Let x_{ikmj} denote the fraction of flow v_{ij} that travels via hub nodes k and m . Furthermore, y_k is a binary decision variable for the selection of hubs. Then

$$v(\text{UHLP}) = \min \sum_{i \in K} \sum_{k \in H} \sum_{m \in H} \sum_{j \in K} v_{ij} c_{ikmj} x_{ikmj} + \sum_{k \in K} f_k y_k, \quad (19a)$$

$$\text{s.t.} \quad \sum_{k \in H} \sum_{m \in H} x_{ikmj} = 1 \quad \forall i, j \in K, \quad (19b)$$

$$x_{ikmj} \leq y_k \quad \forall i, j \in K, \quad k, m \in H, \quad (19c)$$

$$x_{ikmj} \leq y_m \quad \forall i, j \in K, \quad k, m \in H, \quad (19d)$$

$$y_k \in \mathbb{B}, \quad x_{ikmj} \geq 0 \quad \forall i, j \in K, \quad k, m \in H, \quad (19e)$$

formally describes the uncapacitated hub location problem (UHLP). Apparently, if the set of hubs is known a shortest path problem remains to be solved. Otherwise, the problem is NP-hard. Algorithms for solving the uncapacitated hub location problem have been developed, among others, by Klineciewicz (1996), Ernst and Krishnamoorthy (1998), Hamacher et al. (2000) and Mayer and Wagner (2002). The capacitated case is studied by, e.g., Aykin (1994) and Ebery et al. (2000). Hub center problems have recently been studied in Ernst et al. (2002a,b). A survey is given by Campbell (1994b). The problem of locating such interacting hub facilities arises in many applications some of which include airlines (see Campbell, 1992; Aykin, 1995b), the Civil Aeronautics Board (see O’Kelly, 1986, 1987), emergency services (see Campbell, 1994a) and postal delivery services (see Ernst and Krishnamoorthy, 1996).

5.8. Routing location models

The application of the location models discussed so far requires that the cost c_{kj} for allocating the demand d_k of a customer $k \in K$ to a depot can be allocated independently of the allocation of other demand points. A very complex form of service cost depending on each other arises if customers are satisfied within routes covering several customers simultaneously. In this case location and routing decisions are strongly interrelated. Unfortunately, the formulation and solution of routing location models is extremely complicated because of several reasons. First, optimization problems become very complicated. Second, the planning horizons inherent in both subproblems are different. Third, facility location requires to aggregate customers while routing does not. Moreover, besides the variety of facility location models there do exist many different routing models as well (for a survey see Fisher, 1995; Crainic and Laporte, 1998). Hence, a huge number of combined models is possible; to mention a few: Determine an optimal location for a traveling salesman (see Laporte et al., 1983, Simchi-Levi and Berman, 1988, Branco and Coelho, 1990). Combine an UFLP with a matching approach (see Gourdin et al., 2000). Integrate multi-stage facility location, multi-depot vehicle routing and scheduling and fleet mix models (see Jacobsen and Madsen, 1980; Perl and Daskin, 1985; Bookbinder and Reece, 1988; Laporte et al., 1988; Nagy and Salhi, 1996; Salhi and Fraser, 1996; Bruns and Klose, 1996; Bruns, 1998). An in-depth discussion of combined routing location models can be found in Klose (2001). Aykin (1995a) studies hub location and routing problems.

5.9. Multi-objective location models

Strategic planning problems as the allocation of demands and the siting of facilities in distribution networks are often multi-objective in nature. Possible objectives in distribution system design may be, e.g., the minimization of periodic distribution costs, a low level of investment in new facilities, the achievement of a high level in customer service (measured approximately as distances or travel times between customer and depot locations), a “balanced” use of facility capacities, or to avoid large changes to the current system. To some extent multiple objectives may be handled by using cost minimization as a primary goal and modeling other objectives as “soft constraints”; alternative solutions may then be generated by means of relaxing such constraints, changing right-hand sides or objective function coefficients, or by adding additional costs for opening new facilities and closing existing ones. Such an approach does, however, not guarantee that pareto-optimal solutions are found.

While there is a large body of literature on single-objective facility location problems, the work which has been carried out on multi-objective discrete location problems seems to be very limited and is a topic of current research. A number of multi-objective formulations and objectives to be considered in location problems are described in Current et al. (1990). ReVelle (1993) considers a two-objective maximum covering location problem and proposes to weight objectives in order to preserve the “integer-friendly” problem structure. Heller et al. (1989) discuss the use of a p -median model and simulation for locating emergency medical service facilities in case of multiple objectives. ReVelle and Laporte (1996) describe two

alternative formulations for a bicriteria plant location problem, where one objective is to minimize cost and the second objective is to maximize the demand that can be served by a plant within a certain time limit; in order to solve the problem, they also propose the use of a weighting method. Fernández and Puerto (2003) investigate the multi-objective uncapacitated facility location problem; they develop a dynamic programming method as well as an enumerative approach in order to determine the set of pareto-optimal solutions and supported pareto-optimal solutions, respectively.

6. Applications

Applications of facility location models are not restricted to the primary application area of this article, that is, the design of distribution systems (for applications of facility location models to practical problem solving in the area of logistics network design see, e.g., Geoffrion and Graves, 1974; Geoffrion et al., 1982; Gelders et al., 1987; Robinson Jr. et al., 1993; Fleischmann, 1993; Geoffrion and Powers, 1995; Köksalan et al., 1995; Tüshaus and Wittmann, 1998; Engeler et al., 1999; Bruns et al., 2000; Galvão et al., 2002; Boffey et al., 2003; Vasko et al., 2003). By contrast many other problems where location and allocation decisions are interdependent are covered also. For the sake of brevity some of them shall be sketched out as follows:

- **Cluster analysis:** The topic of cluster analysis is to group items in such a way that items belonging to one group are homogeneous and items belonging to different groups are heterogeneous. Location then means to select representative items from the overall set of items while allocation corresponds to the assignment of the remaining items to the chosen clusters. Mulvey and Crowder (1979) model the clustering task as a p -median problem. To the contrary, Rosing (1992a) uses a clustering algorithm in order to solve the MWP heuristically. Moreover, clustering is important in the problem setting of vehicle routing and scheduling (see Fisher and Jaikumar, 1981; Bramel and Simchi-Levi, 1995), and in the area of combined routing location (see Klose and Wittmann, 1995; Klose, 1996).
- **Location of bank accounts:** A company which has to pay suppliers has to decide which bank accounts to use for this purpose. Depending on the location of the used accounts float can be optimized. Cornuejols et al. (1977) model this problem, the so-called account location problem, as an UFLP with the additional constraint (5). Nauss and Markland (1981) study the reverse problem of locating bank accounts in order to receive customer payments, the so-called lock box location problem.
- **Vendor selection:** Each company must choose vendors for the supply of products. Vendor selection is based on multiple criteria such as price, quality, know-how, etc. Location in this setting means selecting some vendors from a given set of vendors. Allocation relates to the decision which product to buy from which vendor. Current and Weber (1994) discuss, among other topics, that this problem can be tackled using well-known location models such as the UFLP and the CFLP.
- **Location and sizing of offshore platforms for oil exploration:** Hansen et al. (1992, 1994) use a capacitated multi-type location model in order to locate offshore platforms for oil exploration. Different platform types relate to potential platform capacities.
- **Database location in computer networks:** Within a computer network databases can be installed on certain nodes. Installation and maintenance of databases gives raise to fixed cost while transmission times or cost may decrease, hence, once more, a certain location-allocation problem arises. Fisher and Hochbaum (1980) model this problem as an extended UFLP.
- **Concentrator location:** The design of efficient telecommunication and computer networks poses several complex, interdependent problems. Related surveys can be found in Boffey (1989), Gavish (1991) and Chardaire (1999). Starlike networks comprise a simple topology, connecting terminals with a central machine. Such a topology is inefficient in the case of many terminals and large distances. Probably, the

installation of concentrators having powerful links to the central machine or another (backbone) network then is necessary. To determine the layout of a concentrator-based network results in a typical location-allocation problem, also called concentrator location problem by Mirzaian (1985) and Pirkul (1987). Chardaire (1999) and Chardaire et al. (1999) study the case where concentrators can be located on two different layers of the network.

- Index selection for database design: Databases comprise a set of tables, each of which consists of several arrays. Relating indices to arrays allows to store entries in a sorted manner yielding fast queries. Caprara and Salazar (1995, 1999) and Caprara et al. (1995) study the index selection problem as an important optimization problem in the physical design of relational databases. Moreover, it is shown that this problem can be formulated as an UFLP (4). Furthermore, efficient branch-and-bound and branch-and-cut algorithms are presented.

References

- Aardal, K., 1998. Reformulation of capacitated facility location problems: How redundant information can help. *Annals of Operations Research* 82, 289–308.
- Aardal, K., Labbé, M., Leung, J.M.Y., Queyranne, M., 1996. On the two-level uncapacitated facility location problem. *INFORMS Journal on Computing* 8, 289–301.
- Aikens, C.H., 1985. Facility location models for distribution planning. *European Journal of Operational Research* 22 (3), 263–279.
- Arora, S., Raghavan, P., Rao, S., 1998. Approximation schemes for Euclidean k -medians and related problems. In: *Proceedings of the 30th Annual ACM Symposium on Theory of Computing*, pp. 106–113.
- Aykin, T., 1994. Lagrangian relaxation based approaches to capacitated hub-and-spoke network design problem. *European Journal of Operational Research* 79, 501–523.
- Aykin, T., 1995a. The hub location and routing problem. *European Journal of Operational Research* 83, 200–219.
- Aykin, T., 1995b. Networking policies for hub-and-spoke systems with applications to the air transportation system. *Transportation Science* 29, 201–221.
- Balas, E., Padberg, M.W., 1976. Set partitioning—A survey. *SIAM Review* 18, 710–760.
- Barcelo, J., Casanovas, J., 1984. A heuristic Lagrangean algorithm for the capacitated plant location problem. *European Journal of Operational Research* 15, 212–226.
- Barcelo, J., Halleffjord, Å., Fernandez, E., Jörnsten, K., 1990. Lagrangean relaxation and constraint generation procedures for capacitated plant location problems with single sourcing. *OR-Spektrum* 12, 79–88.
- Barros, A.I., 1998. *Discrete and Fractional Programming Techniques for Location Models*. Kluwer Academic, London, Dordrecht, Boston.
- Barros, A.I., Labbé, M., 1992. A general model for the uncapacitated facility and depot location problem. Working Paper 92-19, European Institute for Advanced Studies in Management, Brüssel.
- Barros, A.I., Dekker, R., Scholten, V., 1998. A two-level network for recycling sand: A case study. *European Journal of Operational Research* 110, 199–214.
- Bauer, A., Domschke, W., Pesch, E., 1993. Competitive location on a network. *European Journal of Operational Research* 66, 372–391.
- Beasley, J.E., 1988. An algorithm for solving large capacitated warehouse location problems. *European Journal of Operational Research* 33, 314–325.
- Beasley, J.E., 1993. Lagrangean heuristics for location problems. *European Journal of Operational Research* 65, 383–399.
- Benati, S., Laporte, G., 1994. Tabu search algorithms for the $(r|x_p)$ -medianoid and $(r|p)$ -centroid problems. *Location Science* 2, 193–204.
- Berman, O., Larson, R.C., 1985. Optimal 2-facility network districting in the presence of queuing. *Transportation Science* 19, 261–277.
- Boffey, T.B., 1989. Location problems arising in computer networks. *The Journal of the Operational Research Society* 40 (4), 347–354.
- Boffey, T.B., Karkazis, J., 1984. p -medians and multi-mediands. *The Journal of the Operational Research Society* 35 (1), 57–64.
- Boffey, B., Yates, D., Galvão, R.D.G., 2003. An algorithm to locate perinatal facilities in the municipality of Rio de Janeiro. *Journal of the Operational Research Society* 54, 21–31.
- Boland, N., Domínguez-Marín, P., Nickel, S., Puerto, J., 2003. Exact procedures for solving the discrete ordered median problem. Technical Report, Institut Techno- und Wirtschaftsmathematik, Kaiserslautern, Germany.
- Bookbinder, J.H., Reece, K.E., 1988. Vehicle routing considerations in distribution system design. *European Journal of Operational Research* 37 (2), 204–213.

- Bramel, J., Simchi-Levi, D., 1995. A location based heuristic for general routing problems. *Operations Research* 43 (4), 649–660.
- Branco, I.M., Coelho, J.D., 1990. The Hamiltonian p -median problem. *European Journal of Operational Research* 47, 86–95.
- Brandeau, M.L., Chiu, S.S., 1989. An overview of representative problems in location research. *Management Science* 35 (6), 645–674.
- Brimberg, J., Mehrez, A., 1994. Multi-facility location using a maximin criterion and rectangular distances. *Location Science* 2, 11–19.
- Brimberg, J., Hansen, P., Mladenovic, N., Taillard, E., 2000. Improvements and comparison of heuristics for solving the multisource Weber problem. *Operations Research* 48 (3), 444–460.
- Bruns, A.D., 1998. Zweistufige Standortplanung unter Berücksichtigung von Tourenplanungsaspekten—Primale Heuristiken und lokale Suchverfahren. Dissertation Nr. 2152, Universität St. Gallen, Dufourstrasse 50, CH-9000 St. Gallen.
- Bruns, A.D., Klose, A., 1996. A locate first–route second heuristic for a combined location-routing problem. In: *Operations Research Proceedings 1996*. Springer-Verlag, Berlin, Heidelberg, New York, pp. 49–54 (Chapter 3).
- Bruns, A.D., Klose, A., Stähly, P., 2000. Restructuring of Swiss parcel delivery services. *OR-Spektrum* 22, 285–302.
- Campbell, J.F., 1992. Location-allocation for distribution systems with transshipments and transportation economies of scale. *Annals of Operations Research* 40, 77–99.
- Campbell, J.F., 1994a. Integer programming formulations of discrete hub location problems. *European Journal of Operational Research* 72, 387–405.
- Campbell, J.F., 1994b. A survey of network hub location. *Studies in Locational Analysis* 6, 31–47.
- Caprara, A., Salazar, J.J., 1995. A branch-and-cut algorithm for the index selection problem. Technical Report 95-09, DEIS, University of Bologna, Bologna.
- Caprara, A., Salazar, J.J.G., 1999. Separating lifted odd-hole inequalities to solve the index selection problem. *Discrete Applied Mathematics* 92, 111–134.
- Caprara, A., Fischetti, M., Maio, D., 1995. Exact and approximate algorithms for the index selection problem in physical database design. *IEEE Transactions on Knowledge and Data Engineering* 7 (6), 955–967.
- Chandra, P., Fisher, M.L., 1994. Coordination of production and distribution planning. *European Journal of Operational Research* 72, 503–517.
- Chardaire, P., 1999. Hierarchical two level location problems. In: Sansò, B., Soriano, P. (Eds.), *Telecommunications Network Planning*. Kluwer Academic, London, Dordrecht, Boston, pp. 33–54 (Chapter 3).
- Chardaire, P., Lutton, J.-L., Sutter, A., 1999. Upper and lower bounds for the two-level simple plant location problem. *Annals of Operations Research* 86, 117–140.
- Chen, B., Guignard, M., 1998. Polyhedral analysis and decompositions for capacitated plant location-type problems. *Discrete Applied Mathematics* 82, 79–91.
- Chen, P.-C., Hansen, P., Jaumard, B., Tuy, H., 1992. Weber's problem with attraction and repulsion. *Journal of Regional Science* 32 (4), 467–486.
- Chen, P.-C., Hansen, P., Jaumard, B., Tuy, H., 1998. Solution of the multisource Weber and conditional Weber problems by d.-c. programming. *Operations Research* 46 (4), 548–562.
- Cho, D.C., Johnson, E.L., Padberg, M.W., Rao, M.R., 1983. On the uncapacitated plant location problem I: Valid inequalities and facets. *Mathematics of Operations Research* 8, 579–589.
- Christofides, N., Beasley, J.E., 1982. A tree search algorithm for the p -median problem. *European Journal of Operational Research* 10, 196–204.
- Christofides, N., Beasley, J.E., 1983. Extensions to a Lagrangean relaxation approach for the capacitated warehouse location problem. *European Journal of Operational Research* 12, 19–28.
- Chudak, F.A., 1999. Improved approximation algorithms for uncapacitated facility location. In: Bixby, R.E., Boyd, E.A., Ríos-Mercado, R.Z. (Eds.), *Proceedings of the 6th International IPCO Conference*. In: *Lecture Notes in Computer Science*, vol. 1412. Springer-Verlag.
- Chudak, F.A., Shmoys, D.B., 1999. Improved approximation algorithms for a capacitated facility location problem. In: *Proceedings of the 10th Annual ACM-SIAM Symposium on Discrete Algorithms*, pp. 875–886.
- Chudak, F.A., Williamson, D.P., 1999. Improved approximation algorithms for capacitated facility location problems. Technical Report, IBM Watson Research Center.
- Connors, M.M., Coray, C., Cuccaro, C.J., Green, W.K., Low, D.W., Markowitz, H.M., 1972. The distribution system simulator. *Management Science* 18, B425–B453.
- Cornuejols, G., Thizy, J.-M., 1982. Some facets of the simple plant location polytope. *Mathematical Programming* 23, 50–74.
- Cornuejols, G., Fisher, M.L., Nemhauser, G.L., 1977. Location of bank accounts to optimize float: An analytic study of exact and approximate algorithms. *Management Science* 23, 789–810.
- Cornuejols, G., Sridharan, R., Thizy, J.-M., 1991. A comparison of heuristics and relaxations for the capacitated plant location problem. *European Journal of Operational Research* 50, 280–297.
- Crainic, T.G., Laporte, G. (Eds.), 1998. *Fleet Management and Logistics*. Kluwer Academic, London, Dordrecht, Boston.

- Current, J., Weber, C., 1994. Application of facility location modeling constructs to vendor selection problems. *European Journal of Operational Research* 76 (3), 387–392.
- Current, J., Min, H., Schilling, D.A., 1990. Multiobjective analysis of facility location decisions. *European Journal of Operational Research* 49, 295–307.
- Daskin, M.S., 1995. *Network and Discrete Location: Models, Algorithms, and Applications*. Wiley-Interscience Series in Discrete Mathematics and Optimization. John Wiley & Sons, Chichester, New York, Brisbane, Toronto, Singapore.
- Delmaire, H., Díaz, J.A., Fernández, E., 1999. Reactive GRASP and tabu search based heuristics for the single source capacitated plant location problem. *INFOR, Canadian Journal of Operational Research and Information Processing* 37 (3), 194–225.
- Díaz, J.A., 2001. Algorithmic approaches for the single source capacitated facility location problem. Ph.D. Thesis, Dpt. d'Estadística i Investigació Operativa, Universitat Polytechnica de Catalunya, Barcelona, Spain.
- Díaz, J.A., Fernandez, E., 2001. A branch-and-price algorithm for the single source capacitated plant location problem. Technical Report, Dpt. d'Estadística i Investigació Operativa, Universitat Politècnica de Catalunya, Barcelona, Spain.
- Dobson, G., Karmarkar, U.S., 1987. Competitive location on a network. *Operations Research* 35, 565–574.
- Domínguez-Marín, P., Hansen, P., Mladenović, N., Nickel, S., 2003. Heuristic procedures for solving the discrete ordered median problem. Technical Report, Institut Techno- und Wirtschaftsmathematik, Kaiserslautern, Germany.
- Domschke, W., Drexler, A., 1996. *Logistik: Standorte*. Oldenbourg Lehr- und Handbücher der Wirtschafts- und Sozialwissenschaften, fourth ed. R. Oldenbourg Verlag, München, Wien.
- Drezner, Z., 1984. The planar two-center and two-median problems. *Transportation Science* 18, 351–361.
- du Merle, O., Villeneuve, D., Desrosiers, J., Hansen, P., 1999. Stabilized column generation. *Discrete Mathematics* 194, 229–237.
- Ebery, J., Krishnamoorthy, M., Ernst, A., Boland, B., 2000. The capacitated multiple allocation hub location problem: Formulations and algorithms. *European Journal of Operational Research* 120, 614–631.
- Efroymsen, M.A., Ray, T.L., 1966. A branch-and-bound algorithm for plant location. *Operations Research* 14, 361–368.
- Eiselt, H.A., Laporte, G., Thisse, J.-F., 1993. Competitive location models: A framework and bibliography. *Transportation Science* 27, 44–54.
- Engler, K., Klose, A., Stähly, P., 1999. A depot location-allocation problem of a food producer with an outsourcing option. In: Speranza, M.G., Stähly, P. (Eds.), *New Trends in Distribution Logistics*. Lecture Notes in Economics and Mathematical Systems, vol. 480. Springer-Verlag, Berlin, Heidelberg, New York, pp. 95–109 (Chapter 1).
- Erengüç, Ş.S., Simpson, N.C., Vakharia, A.J., 1999. Integrated production/distribution planning in supply chains: An invited review. *European Journal of Operational Research* 115, 219–236.
- Erkut, E., Neuman, S., 1989. Analytical models for locating undesirable facilities. *European Journal of Operational Research* 40, 275–291.
- Erlenkotter, D., 1978. A dual-based procedure for uncapacitated facility location. *Operations Research* 26, 992–1009.
- Erlenkotter, D., 1981. A comparative study of approaches to dynamic facility location problems. *European Journal of Operational Research* 6, 133–143.
- Ernst, A., Krishnamoorthy, M., 1996. Efficient algorithms for the uncapacitated single allocation p -hub median problem. *Location Science* 4, 139–154.
- Ernst, A., Krishnamoorthy, M., 1998. An exact solution approach based on shortest-paths for the p -hub median problems. *INFORMS Journal on Computing* 10, 149–162.
- Ernst, A., Hamacher, H., Jiang, H., Krishnamoorthy, M., Woeginger, G., 2002a. Heuristic algorithms for the uncapacitated hub center single allocation problem. Technical Report, CSIRO, Australia.
- Ernst, A., Hamacher, H., Jiang, H., Krishnamoorthy, M., Woeginger, G., 2002b. Uncapacitated single and multiple allocation p -hub center problems. Technical Report, CSIRO, Australia.
- Fernández, E., Puerto, J., 2003. Multiobjective solution of the uncapacitated plant location problem. *European Journal of Operational Research* 145, 509–529.
- Fisher, M.L., 1995. Vehicle routing. In: Ball, M.O., Magnanti, T.L., Monma, C.L., Nemhauser, G.L. (Eds.), *Network Routing*. In: *Handbooks in Operations Research and Management Science*, vol. 8. North-Holland, Amsterdam, pp. 1–33 (Chapter 1).
- Fisher, M.L., Hochbaum, D.S., 1980. Database location in computer networks. *Journal of the ACM* 7, 718–735.
- Fisher, M.L., Jaikumar, R., 1981. A generalized assignment heuristic for vehicle routing. *Networks* 11 (2), 109–124.
- Fleischmann, B., 1993. Designing distribution systems with transport economies of scale. *European Journal of Operational Research* 70 (1), 31–42.
- Francis, R.L., McGinnis Jr., L.F., White, J.A., 1992. *Facility Layout and Location: An Analytical Approach*, second ed. Prentice-Hall International Series in Industrial and Systems Engineering. Prentice-Hall, Englewood Cliffs, NJ.
- Frantzeskakis, M., Watson-Gandy, C.D.T., 1989. The use of state space relaxation for the dynamic facility location problem. *Annals of Operations Research* 18, 189–212.
- Galvão, R.D., 1996. A Lagrangean heuristic for the maximal covering location problem. *European Journal of Operational Research* 88, 114–123.

- Galvão, R.D., Espejo, L.G.A., Boffey, T.B., 2002. A hierarchical model for the location of perinatal facilities in the municipality of Rio de Janeiro. *European Journal of Operational Research* 138, 495–517.
- Gao, L.-L., Robinson Jr., E.P., 1992. A dual-based optimization procedure for the two-echelon uncapacitated facility location problem. *Naval Research Logistics* 39, 191–212.
- Gao, L.-L., Robinson Jr., E.P., 1994. Uncapacitated facility location: General solution procedure and computational experience. *European Journal of Operational Research* 76 (3), 410–427.
- Gavish, B., 1991. Topological design of telecommunication networks—local access design methods. *Annals of Operations Research* 33, 17–71.
- Gelders, L.F., Pintelon, L.M., van Wassenhove, L.N., 1987. A location-allocation problem in a large Belgian brewery. *European Journal of Operational Research* 28, 196–206.
- Geoffrion, A.M., Graves, G.W., 1974. Multicommodity distribution system design by Benders decomposition. *Management Science* 20, 822–844.
- Geoffrion, A.M., McBride, R., 1978. Lagrangean relaxation to capacitated facility location problems. *AIIE Transactions* 10 (1), 40–47.
- Geoffrion, A.M., Powers, R.F., 1995. Twenty years of strategic distribution system design: An evolutionary perspective. *Interfaces* 25 (5), 105–127.
- Geoffrion, A.M., Graves, G.W., Lee, S.-J., 1982. A management support system for distribution planning. *INFOR, Canadian Journal of Operational Research and Information Processing* 20, 287–314.
- Goetschalckx, M., Vidal, C.J., Dogan, K., 2002. Modeling and design of global logistics systems: A review of integrated strategic and tactical models and design algorithms. *European Journal of Operational Research* 143, 1–18.
- Goldengorin, B., Ghosh, D., Sierksma, G., 2003. Branch and peg algorithms for the simple plant location problem. *Computers & Operations Research* 30, 967–981.
- Gourdin, É., Labbé, M., Laporte, G., 2000. The uncapacitated facility location problem with client matching. *Operations Research* 48 (5), 671–685.
- Grünert, T., 2002. Lagrangean tabu search. In: Ribeiro, C.C., Hansen, P. (Eds.), *Essays and Surveys in Metaheuristics*. Kluwer Academic, Boston, pp. 379–397.
- Guha, S., Khuller, S., 1998. Greedy strikes back: Improved facility location algorithms. In: *Proceedings of the 9th Annual ACM-SIAM Symposium on Discrete Algorithms*, pp. 649–657.
- Guignard, M., 1980. Fractional vertices, cuts and facets of the simple plant location problem. *Mathematical Programming Study* 12, 150–162.
- Guignard, M., 1988. A Lagrangean dual ascent algorithm for simple plant location problems. *European Journal of Operational Research* 35, 193–200.
- Guignard, M., Kim, S., 1983. A strong Lagrangean relaxation for capacitated plant location problems. Working Paper 56, Decision Sciences Department, University of Pennsylvania, The Wharton School.
- Hakimi, S.L., 1964. Optimum locations of switching centers and the absolute centers and medians of a graph. *Operations Research* 12, 450–459.
- Hakimi, S.L., 1965. Optimum distribution of switching centers in a communication network and some related graph theoretic problems. *Operations Research* 13, 462–475.
- Hakimi, S.L., 1983. On locating new facilities in a competitive environment. *European Journal of Operational Research* 12, 29–35.
- Hamacher, H.W., Nickel, S., 1994. Combinatorial algorithms for some 1-facility median problems in the plane. *European Journal of Operational Research* 79, 340–351.
- Hamacher, H.W., Nickel, S., 1998. Classification of location models. *Location Science* 6, 229–242.
- Hamacher, H.W., Labbé, M., Nickel, S., Sonneborn, T., 2000. Polyhedral properties of the uncapacitated multiple allocation hub location problem. Working Paper, Fraunhofer Institut für Techno- und Wirtschaftsmathematik, Kaiserslautern, Germany.
- Handler, G.Y., 1979. Complexity and efficiency in minimax network location. In: Christofides, N., Mingozzi, A., Toth, P., Sandi, C. (Eds.), *Combinatorial Optimization*. John Wiley & Sons, Chichester, New York, Brisbane, Toronto, Singapore, pp. 281–314 (Chapter 10).
- Hanjoul, P., Peeters, D., 1985. A comparison of two dual-based procedures for solving the p -median problem. *European Journal of Operational Research* 20, 387–396.
- Hansen, P., de Luna Pedrosa Filho, E., Ribeiro, C.C., 1992. Location and sizing of offshore platforms for oil exploration. *European Journal of Operational Research* 58, 202–214.
- Hansen, P., de Luna Pedrosa Filho, E., Ribeiro, C.C., 1994. Modelling location and sizing of offshore platforms. *European Journal of Operational Research* 72, 602–606.
- Hansen, P., Mladenovic, N., Taillard, E., 1998. Heuristic solution of the multisource Weber problem as a p -median problem. *Operations Research Letters* 22, 55–62.
- Harkness, J., ReVelle, C., 2003. Facility location with increasing production costs. *European Journal of Operational Research* 145, 1–13.

- Heller, M., Cohon, J.L., ReVelle, C.S., 1989. The use of simulation in validating multiobjective EMS location model. *Annals of Operations Research* 18, 303–322.
- Hindi, K.S., Basta, T., 1994. Computationally efficient solution of a multiproduct, two-stage distribution-location problem. *The Journal of the Operational Research Society* 45 (11), 1316–1323.
- Hindi, K.S., Basta, T., Pieńkosz, K., 1998. Efficient solution of a multi-commodity, two-stage distribution problem with constraints on assignment of customers to distribution centers. *International Transactions in Operations Research* 5 (6), 519–528.
- Holmberg, K., Rönnqvist, M., Yuan, D., 1999. An exact algorithm for the capacitated facility location problems with single sourcing. *European Journal of Operational Research* 113, 544–559.
- Hotelling, H., 1929. Stability in competition. *Economic Journal* 39, 41–57.
- Jacobsen, S.K., Madsen, O.B.G., 1980. A comparative study of heuristics for a two-level routing-location problem. *European Journal of Operational Research* 5, 378–387.
- Käfer, B., Nickel, S., 2001. Error bounds for the approximate solution of restricted planar location problems. *European Journal of Operational Research* 135, 67–85.
- Karkazis, J., Boffey, T.B., 1981. The multi-commodity facilities location problem. *The Journal of the Operational Research Society* 32, 803–814.
- Khumawala, B.M., 1972. An efficient branch and bound algorithm for the warehouse location problem. *Management Science* 18 (12), B718–B731.
- Klamroth, K., 2001. Planar Weber location problems with line barriers. *Optimization* 49, 517–527.
- Klincewicz, J.G., 1996. A dual algorithm for the uncapacitated hub location problem. *Location Science* 4, 173–184.
- Klincewicz, J.G., Luss, H., 1986. A Lagrangian relaxation heuristic for capacitated facility location with single source constraints. *The Journal of the Operational Research Society* 37, 495–500.
- Klincewicz, J.G., Luss, H., Rosenberg, E., 1986. Optimal and heuristic algorithms for multiproduct uncapacitated facility location. *European Journal of Operational Research* 26, 251–258.
- Klose, A., 1993. Das kombinatorische p -Median-Modell und Erweiterungen zur Bestimmung optimaler Standorte. Dissertation Nr. 1464, Hochschule St. Gallen, Dufourstrasse 50, CH-9000 St. Gallen.
- Klose, A., 1996. Using clustering methods in problems of combined location and routing. In: Kleinschmidt, P., Bachem, A., Derigs, U., Fischer, D., Leopold-Wildburger, U., Möhring, R. (Eds.), *Operations Research Proceedings 1995*. Deutsche Gesellschaft für Operations Research e.V. (DGOR), Springer-Verlag, Berlin, Heidelberg, New York, pp. 411–416.
- Klose, A., 1998. A branch and bound algorithm for an uncapacitated facility location problem with a side constraint. *International Transactions in Operational Research* 5, 155–168.
- Klose, A., 1999. An LP-based heuristic for two-stage capacitated facility location problems. *The Journal of the Operational Research Society* 50 (2), 157–166.
- Klose, A., 2000. A Lagrangean relax-and-cut approach for the two-stage capacitated facility location problem. *European Journal of Operational Research* 126 (2), 185–198.
- Klose, A., 2001. Standortplanung in distributiven Systemen. *Physica*, Heidelberg.
- Klose, A., Drexler, A., 2001. Lower bounds for the capacitated facility location problem based on column generation. Technical Report, Universität St. Gallen.
- Klose, A., Wittmann, S., 1995. Facility location based on clustering. In: *Proceedings of the Second International Workshop on Distribution Logistics (IWDL-2)*.
- Köksalan, M., Süral, H., Kirca, Ö., 1995. A location-distribution application for a beer company. *European Journal of Operational Research* 80, 16–24.
- Körkel, M., 1989. On the exact solution of large-scale simple plant location problems. *European Journal of Operational Research* 39, 157–173.
- Korupolu, M.R., Plaxton, C.G., Rajaraman, R., 1998. Analysis of a local search heuristic for facility location problems. Technical Report 98-30, DIMACS, Rutgers University.
- Krarup, J., Pruzan, P.M., 1979. Selected families of location problems. *Annals of Discrete Mathematics* 5, 327–387.
- Krarup, J., Pruzan, P.M., 1983. The simple plant location problem: Survey and synthesis. *European Journal of Operational Research* 12 (1), 36–81.
- Laporte, G., Norbert, Y., Pelletier, P., 1983. Hamiltonian location problems. *European Journal of Operational Research* 12, 82–89.
- Laporte, G., Norbert, Y., Taillefer, S., 1988. Solving a family of multi-depot vehicle routing and location-routing problems. *Transportation Science* 22 (3), 161–172.
- Laporte, G., Louveaux, F., van Hamme, L., 1994. Exact solution to a location problem with stochastic demands. *Transportation Science* 28, 95–103.
- Lee, C.Y., 1996. An algorithm for a two-staged distribution system with various types of distribution centers. *INFOR*, Canadian Journal of Operational Research and Information Processing 34 (2), 105–117.
- Lin, J.-H., Vitter, J.S., 1992. Approximation algorithms for geometric median problems. *Information Processing Letters* 44, 245–249.

- Listes, O., Dekker, R., 2001. Stochastic approaches for product recovery network design: A case study. *Econometric Institute Report EI 2001-08*, Erasmus University Rotterdam.
- Love, R.F., Morris, J.G., Wesolowsky, G.O., 1988. *Facilities Location: Models & Methods*. Publications in Operations Research Series, vol. 7. North-Holland, Amsterdam.
- Marín, A., Pelegrín, B., 1999. Applying Lagrangian relaxation to the resolution of two-stage location problems. *Annals of Operations Research* 86, 179–198.
- Martello, S., Toth, P. (Eds.), 1990. *Knapsack Problems: Algorithms and Computer Implementations*. John Wiley & Sons, Chichester, New York, Brisbane, Toronto, Singapore.
- Mayer, G., Wagner, B., 2002. Hublocater: An exact solution method for the multiple allocation hub location problem. *Computers & Operations Research* 29, 715–739.
- Mazzola, J.B., Neebe, A.W., 1999. Lagrangian-relaxation-based solution procedures for a multiproduct capacitated facility location problem with choice of facility type. *European Journal of Operational Research* 115, 285–299.
- Melachrinoudis, E., 1988. An efficient computational procedure for the rectilinear maximin location problem. *Transportation Science* 22, 217–223.
- Miehle, W., 1958. Link-length minimization in networks. *Operations Research* 6, 232–243.
- Mirchandani, P.B., Oudjit, A., Wong, R.T., 1985. Multidimensional extensions and a nested dual approach for the m -median problem. *European Journal of Operational Research* 21, 121–137.
- Mirzaian, A., 1985. Lagrangian relaxation for the star-star concentrator location problem: Approximation algorithm and bounds. *Networks* 15, 1–20.
- Mulvey, J.M., Crowder, H.P., 1979. Cluster analysis: An application of Lagrangean relaxation. *Management Science* 25 (4), 329–340.
- Nagy, G., Salhi, S., 1996. Nested heuristic methods for the location-routing problem. *The Journal of the Operational Research Society* 47 (9), 1166–1174.
- Nauss, R.M., 1978. An improved algorithm for the capacitated facility location problem. *The Journal of the Operational Research Society* 29, 1195–1201.
- Nauss, R.M., Markland, R.E., 1981. Theory and application of an optimizing procedure for lock box location analysis. *Management Science* 27, 855–865.
- O’Kelly, M.E., 1986. The location of interacting hub facilities. *Transportation Science* 20, 92–106.
- O’Kelly, M.E., 1987. A quadratic integer program for the location of interacting hub facilities. *European Journal of Operational Research* 32, 393–404.
- Ostresh, L.M., 1973. TWIN—exact solutions to the two-source location-allocation problem. In: Rushton, G., Goodchild, M.F., Ostresh, L.M. (Eds.), *Computer Programs for Location-Allocation Problems*. Department of Geography, University of Iowa. pp. 15–28.
- Owen, S.H., Daskin, M.S., 1998. Strategic facility location: A review. *European Journal of Operational Research* 111, 423–447.
- Perl, J., Daskin, M.S., 1985. A warehouse location-routing problem. *Transportation Research* 19, 381–396.
- Pirkul, H., 1987. Efficient algorithms for the capacitated concentrator location problem. *Computers & Operations Research* 14, 197–208.
- Pirkul, H., Jayaraman, V., 1996. Production, transportation, and distribution planning in a multi-commodity tri-echelon system. *Transportation Science* 30, 291–302.
- Pirkul, H., Jayaraman, V., 1998. A multi-commodity, multi-plant, capacitated facility location problem: Formulation and efficient heuristic solution. *Computers & Operations Research* 25 (10), 869–878.
- Pooley, J., 1994. Integrated production and distribution facility planning at Ault foods. *Interfaces* 24, 113–121.
- ReVelle, C., 1986. The maximum capture or “sphere of influence” location problem: Hotelling revisited on a network. *Journal of Regional Science* 26, 343–358.
- ReVelle, C.S., 1993. Facility siting and integer-friendly programming. *European Journal of Operational Research* 65, 147–158.
- ReVelle, C.S., Laporte, G., 1996. The plant location problem: New models and research prospects. *Operations Research* 44 (6), 864–874.
- Robinson Jr., E.P., Gao, L.-L., Muggenborg, S.D., 1993. Designing an integrated distribution system at DowBrands, Inc. *Interfaces* 23 (3), 107–117.
- Rosing, K.E., 1992a. The optimal location of steam generators in large heavy oil fields. *American Journal of Mathematical and Management Sciences* 12 (1), 19–42.
- Rosing, K.E., 1992b. An optimal method for solving the (generalized) multi-Weber problem. *European Journal of Operational Research* 58 (3), 414–426.
- Ryu, C., Guignard, M., 1992a. An efficient algorithm for the capacitated plant location problem. Working Paper 92-11-02, Decision Sciences Department, University of Pennsylvania, The Wharton School.
- Ryu, C., Guignard, M., 1992b. An exact algorithm for the simple plant location problem with an aggregate capacity constraint. Working Paper 92-04-09, Decision Sciences Department, University of Pennsylvania, The Wharton School.

- Salhi, S., Fraser, M., 1996. An integrated heuristic approach for the combined location-vehicle fleet mix problem. *Studies in Locational Analysis* 8, 3–22.
- Scaparra, M.P., 2002. Multi-exchange algorithms for some capacitated facility location problems. Ph.D. Thesis, Department of Computer Science, University of Pisa, Pisa.
- Schilling, D.A., 1980. Dynamic location modeling for public-sector facilities: A multicriteria approach. *Decision Sciences* 11, 714–724.
- Schilling, D.A., Jayaraman, V., Barkhi, R., 1993. A review of covering problems in facility location. *Location Science* 1 (1), 25–55.
- Shetty, B., 1990. Approximate solutions to large scale capacitated facility location problems. *Applied Mathematics and Computation* 39, 159–175.
- Shmoys, D.B., Tardos, E., Aardal, K., 1997. Approximation algorithms for facility location problems. In: *Proceedings of the 29th Annual ACM Symposium on Theory of Computing*, pp. 265–274.
- Shulman, A., 1991. An algorithm for solving dynamic capacitated plant location problems with discrete expansion sizes. *Operations Research* 39 (3), 423–436.
- Simchi-Levi, D., Berman, O., 1988. A heuristic algorithm for the traveling salesman location problem on networks. *Operations Research* 36, 478–484.
- Sridharan, R., 1993. A Lagrangian heuristic for the capacitated plant location problem with single source constraints. *European Journal of Operational Research* 66, 305–312.
- Sridharan, R., 1995. The capacitated plant location problem. *European Journal of Operational Research* 87 (2), 203–213.
- Taillard, E., 1996. Heuristic methods for large multi-source Weber problems. Technical Report IDSIA96-96, IDSIA, Lugano.
- Tcha, D., Lee, B., 1984. A branch and bound algorithm for the multi-level uncapacitated facility location problem. *European Journal of Operational Research* 18, 35–43.
- Thizy, J.-M., 1994. A facility location problem with aggregate capacity. *INFOR, Canadian Journal of Operational Research and Information Processing* 32 (1), 1–18.
- Tragantalerngsak, S., Holt, J., Rönnqvist, M., 1997. Lagrangian heuristics for the two-echelon, single-source, capacitated facility location problem. *European Journal of Operational Research* 102, 611–625.
- Tüshaus, U., Wittmann, S., 1998. Strategic logistic planning by means of simple plant location: A case study. In: Fleischmann, B., van Nunen, J.A.E.E., Speranza, M.G., Stähly, P. (Eds.), *Advances in Distribution Logistics. Lecture Notes in Economics and Mathematical Systems*, vol. 460. Springer-Verlag, Berlin, Heidelberg, New York, pp. 241–263 (Chapter 2).
- Van Roy, T.J., 1986. A cross decomposition algorithm for capacitated facility location. *Operations Research* 34, 145–163.
- Van Roy, T.J., Erlenkotter, D., 1982. A dual-based procedure for dynamic facility location. *Management Science* 28 (10), 1091–1105.
- Vasko, F.J., Newhart, D.D., Stott, K.L., Wolf, F.E., 2003. A large-scale application of the partial coverage uncapacitated facility location problem. *Journal of the Operational Research Society* 54, 11–20.
- Vidal, C.J., Goetschalckx, M., 1997. Strategic production-distribution models: A critical review with emphasis on global supply chain models. *European Journal of Operational Research* 98 (1), 1–18.
- Weber, A., 1909. *Über den Standort der Industrien. 1. Teil: Reine Theorie des Standorts*. Verlag J.C. B. Mohr, Tübingen.
- Weiszfeld, E., 1937. Sur le point pour lequel la somme des distances de n points donnés est minimum. *Tôhoku Mathematical Journal* 43, 355–386.
- Wentges, P., 1994. Standortprobleme mit Berücksichtigung von Kapazitätsrestriktionen: Modellierung und Lösungsverfahren. Dissertation Nr. 1620, Hochschule St. Gallen, Dufourstrasse 50, CH-9000 St. Gallen.
- Wentges, P., 1996. Accelerating Benders' decomposition for the capacitated facility location problem. *Mathematical Methods of Operations Research* 44, 267–290.
- Wesolowsky, G.O., 1993. The Weber problem: History and perspectives. *Location Science* 1 (1), 5–23.