University of Nebraska - Lincoln DigitalCommons@University of Nebraska - Lincoln

Civil Engineering Theses, Dissertations, and Student Research

Civil Engineering

4-2017

Impact-resistant Behavior of Reinforced Concrete Bridge Columns

Chen Fang University of Nebraska-Lincoln, chenfang@huskers.unl.edu

Follow this and additional works at: http://digitalcommons.unl.edu/civilengdiss Part of the <u>Civil Engineering Commons</u>, <u>Construction Engineering and Management Commons</u>, and the <u>Structural Engineering Commons</u>

Fang, Chen, "Impact-resistant Behavior of Reinforced Concrete Bridge Columns" (2017). *Civil Engineering Theses, Dissertations, and Student Research.* 102.

http://digitalcommons.unl.edu/civilengdiss/102

This Article is brought to you for free and open access by the Civil Engineering at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Civil Engineering Theses, Dissertations, and Student Research by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.





Impact-resistant Behavior of Reinforced Concrete Bridge Columns

- bridge.
- the bridge.
- bridge subjected to the combined effect of vehicle collision and blast.
- bridge.





- subjected to vehicle collision and vehicle blast using software LS-DYNA.
- and vehicle blast.
- behaviors of bridge columns

5 spa @ 10'-7 7/16" along the skew Cap 4' x 4'-



Chen Fang, Ph.D. student, Department of Civil Engineering

Advisor: Daniel Linzell, Voelte-Keegan Professor and Chair, Department of Civil Engineering

The University of Nebraska-Lincoln is an equal opportunity educator and employer.

Results (Cont'd)

* The effect of column diameter (including $D_g=2.5ft$, 3.5ft, and 5ft) is considered in the research.



Fig.5. Moment-time curves

Fig.6. Deflection-time curves

Conclusions

- The finite element models including column, pile cap, piles, and soil are feasible and accurate to simulate the responses of bridge columns subjected to vehicle collision.
- ✤ The shear failure plane with 45 degree was initiated at the location of impacting and then propagated through the whole column. The maximum shear occurred at the point of impact.
- The maximum moment of the bridge column increases with the increase in the column diameter, and the increase in the deflection along the column height is also caused by the increase in the column diameter.

Future Work

- To consider vehicle blast in finite element model based on the vehicle collision results.
- To investigate effects of different variables including the spacing of transverse reinforcement, vehicle velocity, and vehicle mass on the responses of bridge column.
- To summarize design considerations for bridge columns subjected to vehicle collision and vehicle blast.

References

✤ Wassef, W., et al. "Comprehensive Design Example for Prestressed Concrete (PSC) Girder Superstructure Bridge with Commentary." Federal Highway Administration report no. FHWA NHI-04-043, grant no. DTFH61-02-D-63006. Washington, DC: US Government Printing Office (2003).













